

COUPLING CROSS REFERENCE

GLOBE DRIVESAVER TO ISOFLEX

DRIVESAVER	ISOFLEX	COMMENTS
303	n/a	
353	n/a	
354	n/a	
404	n/a	
404A	IFC-4300-95	
404AC	IFC-4300-95	2 5/8" Pilot Req'd
404V	IFC-4600-95	
404S	n/a	
424Y	IFC-4200-95	
4756	IFC-6000-95	
4756PR	IFC-6000-HT	
454	n/a	
504	IFC-4500-95	
504A	n/a	
504AC	n/a	
504PR	IFC-4500-HT	
504H	IFC-4550-95	
504HPR	IFC-4550-HT	
524Y	IFC-4400-95	
554	n/a	
908	IFC-8100-95	Iso 1/2" Thicker
908PR	IFC-8100-95	Iso 1/2" Thicker
908S	IFC-8200-95	Iso 1/2" Thicker
n/a	IFC-8200-HT	Iso 1/2" Thicker
908AC	n/a	

DRIVESAVER	ISOFLEX	COMMENTS
1058	IFC-8534-95	
1108	IFC-8695-95	
1108A	IFC-8690-95	
1308	n/a	
4756	IFC-6000-95	
5756	IFC-6100-95	Male Index Ring
5756A	IFC-6125-95	Female Index Ring
5756APR	IFC-6125-HT	Female Index Ring
5756AZF	IFC-6100-95	Male Index Ring
5756AZFPR	IFC-6100-HT	Male Index Ring
5756B	IFC-6150-95	Iso 16mm Bolts
5756T	IFC-6150-95	No Bushing Kit Req'd
6256	n/a	
7256	IFC-6300-95	
7256PR	IFC-6300-HT	
7258ZPR	n/a	
7306Z	IFC-6400-95	IsoFlex 7mm(0.27") Thicker
8078Z	n/a	
8010Z	IFC-10325-95	IsoFlex 7mm(0.27") Thicker
8858Z	n/a	

ALWAYS CHECK TORQUE RATINGS

COUPLING CROSS REFERENCE

POLY FLEX TO ISOFLEX

POLY FLEX	ISOFLEX	COMMENTS
424(90)	IFC-4200-90	
434(90)/(95)	IFC-4300-95	
464(90)/(95)	IFC-4600-95	
484(90)/(95)	IFC-4800-95	
524(90)/(95)	IFC-4500-95	
524FRL	IFC-4550-95	
534(90)/(95)	IFC-4400-95	
546(95)	IFC-6000-95	
547(90)/(95)	IFC-4700-95	
616-1/2 Bolts-M	IFC-6100-95	
616-1/2 Bolts-F	IFC-6125-95	
616-5/8 Bolts	IFC-6150-95	
656	IFC-6150-95	
1550	IFC-4900-95	
2308	IFC-8600-95	
2808	IFC-8700-95	
3408	IFC-8800-95	

POLY FLEX	ISOFLEX	COMMENTS
7206-5/8 Bolts	IFC-6300-95	
7206-3/4 Bolts	IFC-6300-95	ITBK-19-6B
7606	IFC-6400-95	
7606-3/4 Bolts	IFC-6400-95	ITBK-19-6B
7608	IFC-8300-95	
9114	IFC-8200-95	ITBK-22-8B
9114 3+3 IRM	IFC-8200-95	
9858 5/8	IFC-8100-95	ITBK-22-8B
9858 3/4	IFC-8100-95	ITBK-22-8B
9934	IFC-8400-95	
10834	IFC-8534-95	
11834A	IFC-8690-95	
11834	IFC-8695-95	

ALWAYS CHECK TORQUE RATINGS

COUPLING CROSS REFERENCE

R&D TO ISOFLEX

R&D	ISOFLEX	COMMENTS	ISOFLEX COUPLING THINNER BY INCHES
RA900-003	IFC-6000-95		
910-001	IFC-4300-95		0.30
910-002	IFC-4200-95		0.30
910-005	IFC-4300-95	Special Index Ring	0.37
910-006	IFC-6150-95		0.37
910-007	IFC-4600-95		0.74
910-009	IFC-4500-95		0.65
910-012	IFC-4400-95		0.79
910-013	n/a		n/a
910-014	IFC-4300-95		0.30
910-015	n/a		n/a
910-016	n/a		n/a
910-017	IFC-6400-95	ITBK-19-6B	0.89
910-018	IFC-6400-95		0.89
910-019	IFC-4600-95		0.30
910-020	IFC-4600-95		0.30
910-021	n/a		n/a
910-022	IFC-8200-95	ITBK-22-8B	0.25
910-024	IFC-8534-95	ITBK-25-8B	0.46
910-025	IFC-6100-95	Male Index Ring	0.46
	OR		
	IFC-6125-95	Female Index Ring	0.68
910-026	IFC-6150-95		0.46
910-027	n/a		0.00
910-028	n/a		0.00
910-029	IFC-4500-HT		0.94
910-030	n/a		n/a
910-032	IFC-6125-95/a	Female Index Ring	0.68

R&D	ISOFLEX	COMMENTS	ISOFLEX COUPLING THINNER BY INCHES
910-033	IFC-6150-95		0.68
910-034	IFC-4500-95		0.65
910-035	n/a		n/a
910-036	n/a		n/a
910-037	IFC-4500-95		0.89
910-038	n/a		n/a
910-039	IFC-6400-95	ITBK-19-6B	0.99
910-040	IFC-6400-95		0.99
910-041	n/a		n/a
910-042	n/a		n/a
910-043	IFC-4200-90		0.30
910-044	IFC-4500-95		0.65
910-045	n/a		n/a
910-046	IFC-8100-95	ITBK-22-8B	0.25
910-047	n/a		n/a
910-048	IFC-8100-95	ITBK-22-8B	0.97
910-049	n/a		n/a
910-050	IFC-8200-95	ITBK-22-8B	2.50
910-051	IFC-8695-95		0.53
910-052	IFC-6000-95		1.49
910-053	n/a		n/a
910-054	IFC-6100-95	Male Index Ring	0.37
	OR		
	IFC-6125-95	Female Index Ring	0.68
910-055	IFC-4300-95		0.79
910-057	IFC-4500-HT		0.94
910-058	n/a		n/a
910-059	IFC-4600-95		0.42

ALWAYS CHECK TORQUE RATINGS

NOTE: Due to design parameters, R&D Couplings are usually quite a bit thicker than the comparable IsoFlex GEARguard Coupling. Please note these differences in the chart above before ordering. Installing the IsoFlex GEARguard Coupling may require other modifications to drive line components.